FU-MISTER



Adapting to Any Application

Flo-Master delivers up to five times more power than conventional portable vacuums and at an incredible price. Vacuum effectively and with ease as all the germladened air is exhausted completely outside your living area. Install in new construction and existing homes.

Engineered for Everyone

Designed for the best combination of quality, power, and price on the market. From condos to mansions, Flo-Master suits any use.

Built to Last

Designed and assembled in the USA with all steel, powder coated body and with the finest electrical components to exceed your expectations.


Filtered to Flow

Air flow remains strong and motors clean year after year as a result of fine filtration.

Features:

- 3 to 10 Year Transferable Warranty Lifetime on Manufacturing
- Capacity of 5 to 8 Gallons
- 3 Stage Microfiltration
- Ventable Exhaust
- Dual Debris Intake
- All 18 & 20 Gauge Steel
- Powder Coated In & Out
- Sturdy Single & Two-Stud Brackets
 Easy to Hang & Remove
- Outstanding Customer Service
- Variety of Models Available

Designed & Assembled in USA www.builtinvacuum.com 1-800-525-2055



- Less Noise & No Smell
- Ultimate Vacuuming Convenience
- Can be Installed in One Day
- Costs Less than High-end Uprights
- No Retrofit Wall Damage

Flo-Master Warranty

M.D. Manufacturing, Inc. warrants its Flo-Master power units against electrical component failure for a period of ten (10) years. This warranty is transferable with the unit and is not solely limited to the original owner. Any parts (excluding filters) required within the first ten years will be furnished free of charge by the Authorized Dealer from whom the power unit was originally purchased. Models M60 and M80 are warranted for three (3) years. In addition, all Flo-Master units are guaranteed for life against defects in materials and workmanship.

If an Authorized Dealer is not nearby, M.D. Manufacturing, Inc. will honor and perform required warranty services. The end user must return the unit to the factory freight pre-paid. This warranty does not apply to applications outside of North America, commercial applications, misuse, abuse, acts of God, operating without the filters, or units tampered with by unauthorized personnel.

Exterior Venting

Venting not required but optional. When venting M92, vent both exhaust ports. Exterior venting is required for confined locations.

M80 Requirement

The included air relief valve must be installed on one of the intakes.

M85 Requirement

The included air relief valve must be installed on the backside of the unit in the air relief opening.

*Factors other than air watts should be taken into consideration including: altitude, amount of hours of daily usage, complexity of pipe installation, length of furthest vacuum inlet, noise level desired, type and size of filtration, country of origin, construction materials, and budget. The square footage recommendations on this page are solely based upon the suction capabilities of the unit.









Designed & Assembled in USA All Steel Construction

Flo-Master Models MD Part #	M80 120v F1156MF	M32 120v F1254NC	M85 120v F1156AC	C650 120v F1155AJ	M92 240v F2258NH
Motor	Single 5.7", 1-stg.	Dual by-pass 5.7", 2-stg.	Single 5.7", 2-stg.	Single by-pass 5.7", 2-stg.	Dual by-pass 5.7", 3-stg.
Max Air Watts	453	495	650	653	943
Max Amps	10.2	16	14.9	16	13.7
Waterlift	108"	84"	143"	148"	137"
CFM @ 2" opening	119.5	166	130	130	191
Voltage	120	120	120	120 240 option	240 120 option
Height	20"	28"	33"	39.5"	30"
Weight	17 lbs.	38 lbs.	34 lbs.	29 lbs.	40 lbs.
Trash Capacity	5 gal.	8 gal.	8 gal.	5 gal.	8 gal.
Filtration Type	Microfilter	Hyperflow or Closed Bag	Hyperflow or Closed Bag	Inverted Cloth & Closed Bag	Hyperflow or Closed Bag
Max Ft ²	3,000*	6,000*	8,000*	8,000*	20,000*
Warranty	3 Year Transf. + Lifetime	10 Year Transferable + Lifetime			
Protection	Resettable Minibreaker				
Construction	18 & 20 Gauge Steel (C650 Plastic Bucket)				
Finish	Powder Coat				

